





IS3N-20/IS4N-20

IS3N-32/IS4N-32

IS4N-40/IS4N-63

IS4N-100

IS3N-20

Weathersafe Rotary Isolator Switch - 3 Pole 20Á

- Three pole 20A switch.
- Solid Neutral.
- On load switch disconnectors.
- To BS EN 60947-3.
- Switch can be removed from DIN rail assembly allowing quick and easy first fix.
- Interlocked front cover can only be removed when in OFF position.
- Lockable switch prevents tampering.
- IP65 weatherproof rating.
- Tough durable thermoplastic construction.
- Cable entry knockouts on enclosures.

IS4N-20

Weathersafe Rotary Isolator Switch - 4 Pole 20A

Shares the features and benefits of the IS3N-20 but is 4 pole 20A.

Four pole 20A switch.

IS3N-32

Weathersafe Rotary Isolator Switch - 3 Pole 32Á

■ Three pole 32A switch.

IS4N-32

Weathersafe Rotary Isolator Switch - 4 Pole 32Á

Four pole 32A switch.

IS4N-40

Weathersafe Rotary Isolator Switch - 4 Pole 40Å

Four pole 40A switch.



All these products carry a 3 year guarantee.



See pages 92 – 93 for product specifications.

IS4N-63

Weathersafe Rotary Isolator Switch - 4 Pole 63Á

■ Four pole 63A switch.

IS4N-100

Weathersafe Rotary Isolator Switch - 4 Pole 100A

Four pole 100A switch.



Clear and Simple

Designed with safety in mind, the interlocked front covers can only be removed when in the OFF position. Lockable switch prevents tampering.



P65RATING Weathersafe

IP65 Rotary Isolators keep you safe!

The Weathersafe Rotary Isolator range is manufactured from tough, durable thermoplastic for outdoor switching protection.

3 and 4 pole, 20A to 100A versions available with multiple cable entry knockouts on enclosures.







EASZKN

NEW Product

EASZKN

Emergency Assist Alarm System Kit -Single Zone

Single zone control panel kits are available for where assistance may be required in WC areas, changing rooms, bedrooms etc. With 2 wire connection between control panel, pull cord, reset button and over door light, installation couldn't be simpler, making it a must-have for new installations and existing conversions.

- Suitable for use where assistance may be required in WC areas, changing rooms, bedrooms etc.
- Each kit includes:
- 1x single zone control panel 2 gang.
- 1x reset button Single gang. ■ 1x over door light – Single gang.
- 1x pull cord.
- 1x disabled sticker.
- Simple 2 wire connection from control panel to kit components.
- Slimline design.
- Control panel features audible and visual alerts.
- Illuminated reset button clearly marked, also in Braille.
- Illuminated over door light with audio output.
- Pull cord comes with ceiling mounted housing and 2m cord.
- This is a stand-alone kit that must be used in its entirety and cannot be mixed with additional components.







EACP1N

Single Zone Control Panel - 2 Gang

- Single zone systems ideal for WC's and rooms in the home, shop conversions and small businesses.
- Continuous high dB Control Panel alarm with audible and visual alerts.
- Control Panel fits standard BS flush 2 gang or surface mounted boxes.

Complies with: EN60335-1: Household and similar electrical installations – safety. BS8300: The Design of buildings and their appliances to meet the needs of disabled people – Code of practice.







EARB1N

EARB1N

Single Zone Reset Button - Single Gang

- Illuminated reset button clearly marked, also in Braille.
- Reset button fits standard BS flush or surface mounted boxes.







EADF1N

EADF1N

Single Zone Over Door Light

Illuminated over door light with audio output.



EAPC1N

Single Zone Pull Cord

EADS

Disabled Sticker

Self-adhesive disabled sticker.





