



MTLW3000
LEDs
UP TO
140W

MTLW3000/SLW2400



LEDs
UP TO
140W

MLB3000/MLW3000



LEDs
UP TO
80W

NSLDD1000

MTLW3000
3000W PIR Light Controller

- 12m detection range with 200° area of detection.
- Adjustable light level control.
- IP55 weatherproof rating.
- Adjustable light ON time 5 seconds to 18 minutes.
- Manual ON/OFF override.
- Hinged back box for ease of wiring.
- Total PIR switching: 3000W halogen/incandescent, 500W fluorescent/low energy plus 140W LED.

SLW2400
2000W PIR Light Controller

- 12m detection range with 180° area of detection.
- IP44 weatherproof rating.
- Adjustable light ON time 5 seconds to 18 minutes.
- Manual ON/OFF override.
- Total PIR switching: 2000W incandescent/halogen, 500W fluorescent/low energy.

MLB3000
3000W PIR Light Controller – Black

- 12m detection range with 200° area of detection.
- Light ON times adjustable from 5 seconds to 18 minutes.
- Scrolling LED 'System Live' status acts as advance deterrent.
- Adjustable light level control.
- Manual ON/OFF override.
- Optional holiday mode between 1 and 8 hours.
- Direct mount bracketless fixing – contractor quick fit aid supplied.
- IP55 weatherproof rating.
- Total PIR switching: 3000W halogen/incandescent, 500W fluorescent/low energy plus 140W LED.

MLW3000
White Version

Shares all the features and benefits of the MLB3000 but is available in a white finish.

MLSA360N
360° PIR Light Controller

- Adjustable PIR detector with pan and tilt sensor aiming adjustment.
- Enhanced 360° detection zone for optimum coverage.
- Up to 12m detection range at 2.8m mounting height.
- Light ON time adjustment 5 seconds to 12 minutes.
- LUX (light level) adjustment – Day to Night (5 to 1000 LUX – permanently ON when at max.).
- Total PIR switching 3000W incandescent/halogen, 500W fluorescent, and 140W LED lighting.
- IP45 weatherproof rating.
- Corner mount bracket supplied in pack.
- Easy installation with Fast-fix terminal block connection.

NSLDD1000
3000W Dusk to Dawn Light Controller

- Hinged front cover for ease of wiring.
- Dusk light level adjustment.
- Light ON time is adjustable in 5 steps (2, 4, 6, 8 hours or until dawn).
- IP55 weatherproof rating.
- Switching delay avoids nuisance switching.
- Total light switching: 3000W incandescent/halogen, 500W fluorescent/low energy plus 80W LED.



LEDs
UP TO
500W

MPLP180BK/MPLP180WH

MLTP180BK
2300W 180° PIR Anti Tamper Light Controller – Black

- Tamper proof design.
- 180° 12 metre detection.
- IP55 weatherproof rating.
- Adjustable time setting – 2 seconds to 30 minutes.
- Adjustable 2 to 1000 LUX setting.
- 2300W halogen, 500W fluorescent and LED switching.
- Optional corner bracket.

MLTP180WH
White Version



LEDs
UP TO
250W

SLB2300/SLW2300



LEDs
UP TO
250W

SLB2300RF/SLW2300RF



LEDPROF0B

SLB2300
2300W PIR Light Controller – Black

- Powerful PIR controller for new and existing installations.
- Total PIR switching: 2300W incandescent/halogen, 500W fluorescent/low energy plus 250W LED.
- 12m detection range with 180° area of detection.
- Pan and tilt feature.
- Light ON times adjustable from 5 seconds to 15 minutes.
- LUX (light level) adjustment – Day to Night (2 to 1000).
- Manual ON/OFF switching override.
- IP55 weatherproof rating.
- Simple and quick to fit terminal block connectors.
- Dimensions: 93 x 78 x 141mm.
- Corner mounting bracket available – SLBCB.

SLW2300
White Version

- Corner mounting bracket available – SLWCB.

SLB2300RF
2300W PIR Light Controller c/w RF Control – Black

- 180° up to 12 metre detection.
- Pan and tilt feature.
- Adjustable time setting 3 Seconds – 18 Minutes.
- Adjustable 2 – 1000 LUX setting.
- IP55 weatherproof rating.
- Total PIR switching:
 - 2300W Halogen Lighting.
 - 500W Fluorescent Lighting.
 - 250W LED Lighting.
- Corner mounting bracket available – code SLBCB.
- RF Fob control, up to 100m handheld range.
- Up to 6 remote fobs can be used with each PIR.
- Fob can also fit into a standard indoor/outdoor wall switch, eliminating the need to hard wire the PIR override switch.

SLW2300RF
2300W PIR Light Controller c/w RF Control – White

- Corner mounting bracket available – SLWCB.

LEDPROF0B
LEDPRO RF Remote Fob

- Eliminates the need for hard wired PIR override.
- RF key Fob remote control – 100m range.
- Can be surface mounted and used as a wall switch – 10m range.
- Up to 6 remotes can be used with one PIR.
- Auto learn.
- Battery: 3V (1x CR2032).
- IP44 weatherproof rating.
- Compatible with Timeguard PIR sensor models: LEDPRORFKB, LEDPRORFKWH, SLB2300RF and SLW2300RF.

SLB/SLW2300RF
PIR with built-in RF Receiver for use with RF Remote Control Fob (included)



Works with up to 6x RF remote control fobs.



Fob fits to standard indoor/outdoor wall switch for quick installation.



SLBCB
Corner Bracket for SLB2300 and SLB2300RF

- Simply screw fit to wall with controller's wall plate and click fit controller into position.
- Ideal for narrow passageways and corner entrance/exit points.

SLWCB
Corner Bracket for SLW2300 and SLW2300RF

Goto SPECIFICATIONS
See page 83 for product specifications.

3 YEAR GUARANTEE INCLUDED
All these products carry a 3 year guarantee.



LEDs
UP TO
140W

MLSA360N