



Active BLUE BUTTON
RCD05WAV

RCD05WAV **BLUE**
Valiance® RCD Twin White Socket – Active

Twin socket RCD circuit breaker simply replaces an existing twin socket providing two protected switched socket outlets. The contacts break when power supply is temporarily lost.

- Protects appliances from possible fire hazard.
- Manual reset and test button for safety checks.
- Extra fast action – trips out within 40 milliseconds (BS7288).
- Automatically disconnects both Live and Neutral connections leaving Earth connection intact.
- Trips out when the power supply is temporarily lost. A safety must for machine tool applications.
- Still protects with lost Neutral.
- Still protects with pulsating DC earth fault currents.
- Complies with BS7288 and BS1363.

RCD06WPV **GREY**
Valiance® RCD Twin White Socket – Passive

Shares all the features and benefits of the RCD05WAV but remains latched when the power supply is temporarily lost.



RCD16ML **Passive GREY BUTTON**



Active BLUE BUTTON
RCD07MAV

RCD07MAV **BLUE**
Valiance® RCD Twin Metal Socket – Active

Twin socket RCD circuit breaker with strong metal construction, ideal for use in factories and other industrial environments where protection against shock and fire hazard is essential.

- Supplied with a 40mm BS metal surface wall box.
- Provides two protected switched socket outlets for convenience and extra safety.
- Manual reset and test button for safety checks.
- Extra fast action – trips out within 40 milliseconds (BS7288).
- Automatically disconnects both Live and Neutral connections leaving Earth connection intact.
- Trips out when the power supply is temporarily lost. A safety must for machine tool applications.
- Still protects with lost Neutral.
- Still protects with pulsating DC earth fault currents.
- Complies with BS7288 and BS1363.
- Supplied with a 40mm BS metal surface wall box.

RCD08MPV **GREY**
Valiance® RCD Twin Metal Socket – Passive

Shares all the features and benefits of the RCD07MAV but remains latched when the power supply is temporarily lost.

RCD16ML **GREY**
RCD Metal Fused Connection Unit – Passive

Shares all the features and benefits of the RCD10WPV but in metal, supplied with a 40mm BS metal surface wall box.

5 YEAR GUARANTEE INCLUDED
All Valiance products carry a 5 year guarantee.



Passive GREY BUTTON
RCD10WPV

RCD10WPV **GREY**
Valiance® RCD White Fused Connection Unit – Passive

RCD Fused Connection Unit for additional protection against electric shocks and fire risk. The unit will remain latched if the power supply is tripped.

- Provides additional protection against the dangers of electrocution.
- Eliminates the need for plug-in residual current circuit breakers.
- Protects appliances from possible fire hazard.
- Extra fast action – trips out within 40 milliseconds (BS7288).
- Latching for continuous operation after supply interruption.
- Disconnects both Live and Neutral connections leaving Earth connection intact.
- Complies with BS7288.



WEATHERSAFE IP66 RATING
TGV101N

TGV101N
Weathersafe Vision Single Gang 13A Switched Socket

The safest way to take power outdoors. There is no need for running extension cables outside as it features a fully IP66 weatherproof casing with a see-through clear plastic cover and a highly visible power ON indicator. It can be safely used with the lid closed, keeping you fully aware of the power status to your lawnmower, power tool or other appliance.


- Weathersafe 'Vision' see-through clear plastic cover.
- Single gang switched socket – suitable for all 13 amp BS plugs.
- Lockable cover facility.
- Impact resistant housing.
- Easy release lid catch.
- Multiple M20 threaded screw-outs.
- Power 'ON' neon indicator clearly visible when lid closed.
- Spacious design allowing full closure of lid with plug in position.
- Complies with BS1363.
- IP66 weatherproof rating.



On all selected products.

FSTWIFITGV
Wi-Fi Controlled IP66 Fused Spur

- Available for Android and iOS only, works with Wi-Fi and 4G.
- Supports multiple devices and multiple users.
- Can reduce running costs if unwanted programmes are cancelled.
- Operating voltage 230V 50Hz.
- 13A rated suitable for 3kW:
 - Immersion heaters.
 - 5A inductive load.
 - 1000W tungsten.
 - 500W LED.
 - 100W CFL.
 - 500W Fluorescent.
- Manual override.
- Replaceable 13 Amp BS1362 fuse.
- Item pre-fitted into IP66 enclosure.
- Double pole isolating switch.
- Operating temperature 0 to 40°C.



WEATHERSAFE IP66 RATING
TGV103N

TGV103N
Weathersafe Vision Single Gang 13A Fused Spur

Weathersafe Vision Fused Spur to control pond pumps, fountains and other permanent outdoor installations. As well as an ON/OFF switch it is fitted with a 13A fuse link and complies with BS1363.

- Weathersafe 'Vision' see-through clear plastic cover.
- Fitted with 13A fuse link.
- Lockable cover facility.
- Impact resistant housing.
- Easy release lid catch.
- Multiple M20 threaded screw-outs.
- Power 'ON' neon indicator showing switch status.
- Complies with BS1363.
- IP66 weatherproof rating.



YouTube support available on this product.



All Weathersafe products carry a 3 year guarantee.

See pages 88 – 89 for product specifications.



FSTWIFITGV